

INTELLIGENT SPRAYERS

SEAFLO brand sprayer is intelligent and efficient with one-click start function, saying goodbye the manual. The translucent tank made of a solid HDPE material ensures longer life and easy visibility of the liquid in the tank; and rugged design makes uniform thickness and impact resistance. Automatic high-pressure water pump makes spraying longer distance and spraying uniform. Our product quality is reliable, and it is exported to markets such as Europe, America, Australia, Canada and Southeast Asia. It is your good helper in garden irrigation.

12VOLT KNAPSACK SPRAYERS

16LITER 12VOLT KNAPSACK SPRAYERS

STANDARD PUMP CONFIGURATIONS

Model	SFESR-16A-01
Capacity	16L
Pump	2.6LPM / 70PSI
Battery	12V / 4.5AH
Battery Charger	14V / 1A
Water Hose	1.2M
Pressure Switch	●
Charging Stand	●
Handel Switch	●
Fan Nozzle	●
Double Nozzle	●
G.w	6.6kgs
Size (mm)	330X220X550
Packing Size (mm)	696x360x610
20GP	510pcs
40HQ	1293pcs



12 VOLT ATV SPRAYERS

50, 100 LITER 12 VOLT SPRAYERS



STANDARD PUMP CONFIGURATIONS

Model	Description	Pump	Size	Weight (dry)	Packing Size	20GP	40HQ
SFSP-050-010-01A(B)	50L	3.1 LPM 80 PSI	734x340x425.5mm	8.0kgs	740x355x445mm	217pcs	550pcs
SFSP-050-013-01A(B)	50L	5.0 LPM 100 PSI	734x340x425.5mm	10.0kgs	740x355x445mm	217pcs	550pcs
SFSP-100-013-01A(B)	100L	5.0 LPM 100 PSI	910x410x500mm	14.0kgs	920x420x560mm	113pcs	285pcs

A without Pressure Regulating Valve, **B** with Pressure Regulating Valve. Consult factory for other available models.

AUTO SHUT OFF FUEL CANS

Seaflo 5, 10 & 20 Litre automatic shut off fuel cans which are designed with specially proportioned rear handle for balanced pouring that is self venting for safer & easier pouring. Features reduced emissions to protect the environment and meets EAP & AS/NZS 2906:2001 Standards




TYPICAL APPLICATIONS

Car, lawnmower, atv or snowblower and other essential equipment topped off with fuel

FEATURES

Complies to EPA & CARB Standards
Spill Proof, Durable Vented Pouring Spout
UV Stabilized High Grade Polyethylene
Certified to Australian Standard AS/NZS 2906:2001



STANDARD PUMP CONFIGURATIONS

Model	Capacity	Size	Weight	Fuel	Color	Handle Type	Packing Size	20GP	40HQ
SFGT-05-01	5L	260x130x275mm	0.8kgs	Gasoline	Red	Built-in	530x405x285mm	2382pcs	6048pcs
SFGT-10-01	10L	290x160x346mm	1.3kgs	Gasoline	Red	Built-in	610x505x355mm	1320pcs	3342pcs
SFGT-20-01	20L	330x190x476mm	1.8kgs	Gasoline	Red	Built-in	675x385x485mm	796pcs	2020pcs
SFDT-05-01	5L	260x130x275mm	0.8kgs	Diesel	Yellow	Built-in	530x405x285mm	2382pcs	6048pcs
SFDT-10-01	10L	290x160x346mm	1.3kgs	Diesel	Yellow	Built-in	610x505x355mm	1320pcs	3342pcs
SFDT-20-01	20L	330x190x476mm	1.8kgs	Diesel	Yellow	Built-in	675x385x485mm	796pcs	2020pcs
SF2T-05-01	5L	260x130x275mm	0.8kgs	Engine	Green	Built-in	530x405x285mm	2382pcs	6048pcs
SF2T-10-01	10L	290x160x346mm	1.3kgs	Engine	Green	Built-in	610x505x355mm	1320pcs	3342pcs
SF2T-20-01	20L	330x190x476mm	1.8kgs	Engine	Green	Built-in	675x385x485mm	796pcs	2020pcs