



Marine Equipment  
Catalog Download



Marine Lighting  
Catalog Download



Ultrasonic Defense System  
Catalog Download



## FUJIAN AIDI ELECTRIC CO.,LTD.

Office Add: No.520 Hengtian Road, Business Operation Center in North Station, Jimei District, Xiamen, Fujian, China

Factory Add: F2-4 Block, Industrial Park, Liancheng County, Longyan City, Fujian, China

Tel / WhatsApp / Wechat: + 86 13860382108

Web: [www.seaflo.com](http://www.seaflo.com) [www.seaflomariner.com](http://www.seaflomariner.com)

E-mail: [business@seaflo.com](mailto:business@seaflo.com)



Wechat



Website



WhatsApp

### ACCURACY AND COMPLETENESS OF INFORMATION

All information in this literature regarding products and services provided by SEAFLO is subject to change without prior notice. Reasonable efforts are taken to ensure the accuracy and integrity of all information provided here, but SEAFLO is not responsible for misprints, out-of-date information, or errors. SEAFLO makes no warranty, express or implied, or assumes any legal liability or responsibility for the accuracy or completeness of any information contained in this literature.

# SEAFLO®

— Make Water Work For You —



## MARINE LIGHTING



2026  
MASTER CATALOGUE

[www.seaflo.com](http://www.seaflo.com)

USCG ABYC COLREG 72 ISO8846





<b>2008</b> Brand Created in	<b>4 Million</b> Annual Capacity	<b>160,000</b> Square meters	<b>1000+</b> Customers	<b>240+</b> Patents
---------------------------------	-------------------------------------	---------------------------------	---------------------------	------------------------

SEAFLO group is an ISO 9001, BSCI certified, professional marine & RV integrated accessories solution and outdoor solution provider and manufacturer. We have 3 production bases, 3 modern standard workshops of 50,000 square meters, and more than 200 employees. SEAFLO products and brand is deeply engaged in Marine, RV and outdoor market for more than a decade. We offer professional and reliable service with the cost-effective products of SEAFLO brand and private branding for our partners.

We serve more than 1000 customers in over 100 countries all over the world. We are committed to build a strong and senior technical personnel of research & development team.

We have obtained more than 200 domestic and international patents, and our products have passed CE, UKCA, LFGB, USCG, ABYC, COLREG 72, ROHS, ISO 8846 and ISO 8849, CSA, Reach, PAHs and other international certifications.

**Our Mission:** A community of ordinary people, buiding an extraordinary company with value and warmth.

**Our Vision:** To become a globally influential brand that leads sustainable growth through 2050 and beyond.(2020-2050)

**Our Values:** Time Tests Value. Co-creation Shapes Tomorrow. -Learning, Growing, Giving Thanks, Winning Together.

# CONTENTS

## Searchlight

	LED Aluminum Searchlight 04/05 Series .....03
	Remote Control LED Searchlights .....05
	Remote Control Halogen Searchlights .....09

## Navigation Light

	LED Multi-Function Sport Lights.....11
	LED Portable Navigation Light Kits .....12
	LED Navigation Lights 03/04 Series .....13
	LED Square Navigation Light 01/02 Series .....15
	Horizontal Mount Lights 05 Series .....17
	Vertical Mount Lights 05/06 Series .....17
	Deck Mounted Navigation Lights .....19
	Vertical Mount Lights 02/04 Series .....20
	Horizontal Mount Lights 02/03/04 Series .....21
	LED Bi-Color Bow Light .....22

## LED All-Round Pole Lights

	LED All-Round Lights 01 Series .....22
	LED All-Round Lights 02 Series .....24
	LED All-Round Pole Lights 05 Series .....24

	LED All-round Pole Lights 06 Series .....29
	Mounting Base for Plug-in Mount Pole Lights .....31
	LED Bi-color Bow Lights .....32
	LED All-Round Pole Lights 01/02/03/04 Series .....33
	Mounting Base for Pole Lights .....36

## Led Underwater Lights

	Underwater Lights 01/02 Series .....38
---	--

## LED Floodlights

	LED Floodlights 02/03/04 Series .....41
	Dual Colour LED Floodlights 01 Series .....42
	LED Floodlights 3/6/12 LEDs .....43
	LED Floodlights 07/08 Series .....45
	LED Deck Lights .....46

## Interior Lighting

	LED Stern Lights 01/02 Series .....47
	LED Strip Lights .....48
	LED Ceiling Lights .....48
	LED Courtesy Lights .....51
	LED Livewell Lights .....52
	LED Reading Lights .....53



### IMO COLREG 72 Lights and Visibility - Sailboats

IMO COLREG requirements for navigation lighting on powerboats less than 50m (165ft) LOA (Length Overall).  
Note - Sailboats under motor adopt the rules for Powerboats.

**Powerboats up to 7m (23ft).**  
Not capable of more than 7 knots



- 1x All Round White

**Powerboats up to 12m (39.6ft)**  
Where Separate Masthead and Stern cannot be mounted



- 1x Port lamp (2NM)
- 1x Starboard lamp (2NM)
- OR
- 1x Bi-Colour lamp (2NM)
- 1x All Round White lamp (2NM)

**Powerboats up to 12m (39.6ft)**



- 1x Port lamp (2NM)
- 1x Starboard lamp (2NM)
- OR
- 1x Bi-Colour lamp (2NM)
- 1x Masthead lamp (2NM)
- 1x All Round White lamp (2NM) for vessels at anchor
- 1x Stern lamp (2NM)

**Powerboats more than 12m (39.6ft), but less than 20m (66ft)**



- 1x Port lamp (2NM)
- 1x Starboard lamp (2NM)
- OR
- 1x Bi-Colour lamp (2NM)
- 1x Masthead lamp (3NM)
- 1x Stern lamp (2NM)
- 1x All Round White lamp (2NM) for vessels at anchor

**Powerboats more than 20m (66ft), but less than 50m (165ft)**



- 1x Port lamp (2NM)
- 1x Starboard lamp (2NM)
- 1x Masthead lamp (5NM)
- 1x Stern lamp (2NM)
- 1x All Round White lamp (2NM) for vessels at anchor

### IMO COLREG 72 Lights and Visibility - Sailboats

IMO COLREG requirements for navigation lighting on sailboats less than 50m (165ft) LOA (Length Overall).  
Note - Sailboats under motor adopt the rules for Powerboats.

**Sailboats up to 20m (66ft) under sail**



- 1x Tri-Colour lamp (2NM)
- 1x Masthead lamp (3NM)
- 1x All Round White lamp (2NM) for vessels at anchor


**Sailboats more than 20m(66ft) but less than 50m(165ft) under sail**



- 1x Port lamp (2NM)
- 1x Starboard lamp (2NM)
- OR
- 1x Bi-Colour lamp (2NM)
- 1x Stern lamp (2NM)
- 1x Masthead lamp (5NM)
- 1x All Round White lamp (2NM) for vessels at anchor


The following images depict ADDITIONAL lighting requirements for special activities:

**Sailboats and Powerboats grounded**




- 1x All Round White lamp (2NM)
- 2x All Round Red lamp (2NM) Mounted above one another

**Sailboats and Powerboats not under command (NUC)**



- 2x All Round Red lamp (2NM) Mounted above one another

**Sailboats and Powerboats manoeuvring with difficulty (RAM)**



- 1x All Round Red lamp (2NM)
- 1x All Round White lamp (2NM)
- 1x All Round Red lamp (2NM) Mounted above one another

## LED Aluminum Searchlight 05 Series

- IP65 rated
- Precise beam tilt control: 20° up, 20° down, rotation: 360° continuous
- Dual-speed adjustable modes (fast/slow switching)
- Remote control and 15ft / 4.6m cable included
- Equipped with high-efficiency CREE LEDs, providing up to 50,000 operating hours
- Robust die-cast aluminum housing, triple-coated & UV stabilized, fully enclosed design



**CREE LED**

**CREE LED**  
high-lumen chips, long-lasting high intensity, stable lighting performance



**Beam Distance: 600m**



## LED Aluminum Searchlight 04 Series

- IP65 rated
- Precise beam tilt control: 9° up, 17° down,
- Rotation: 360° continuous
- Dual-speed adjustable modes (fast/slow switching)
- Equipped with high-efficiency CREE LEDs, providing up to 50,000 operating hours
- Remote control and 15ft / 4.6m cable included
- Robust die-cast aluminum housing, triple-coated & UV stabilized, fully enclosed design





**CREE LED**

**CREE LED**  
high-lumen chips, long-lasting high intensity, stable lighting performance



**Beam Distance: 1000m**



left and right 360° continuous rotation



Built-in elevation rotation structure, Up 20°, Down 20°



Powerful 6-LED array delivers an ultra-bright beam



Three-layer coating protection (Salt Spray, Humidity, Weather Resistance)



left and right 360° continuous rotation



Built-in elevation rotation structure, Up 9°, Down 17°



Powerful 9-LED array delivers an ultra-bright beam



Three-layer coating protection (Salt Spray, Humidity, Weather Resistance)

Model	Control Type	Voltage	Power	Color Temperature	Luminous Flux	Candlepower	Beam Distance	Housing Material
SFSL3-2700W-05W	Wired remote	12/24V	25W	5000K (White)	2700 lm	100000 cd	600m	Die-cast aluminum alloy
SFSL3-2700W-05WA	Wireless remote							

Up and down 40° rotation, left and right 360° continuous rotation

Model	Control Type	Voltage	Power	Color Temperature	Luminous Flux	Candlepower	Beam Distance	Housing Material
SFSL3-3000W-04W	Wired remote	12/24V	36W	5000K (White)	3000 lm	220000 cd	1000m	Die-cast aluminum alloy
SFSL3-3000W-04WA	Wireless remote							

Up 9° and down 17° rotation, left and right 360° continuous rotation



**SEOUL**  
**SEOUL LED**  
 delivers high lumen output, high current operation capability, and stable, long-lasting performance.

## Remote Control LED Searchlight

SEAFLO searchlights can perform omnidirectional, multi-angle, and long-distance lighting tasks. They can rotate 360 degrees horizontally and 60 degrees vertically. Equipped with a remote control and multifunction settings for user convenience, these searchlights are ideal for mariners locating buoys, moorings, channel markers, and more.

### FEATURES & BENEFITS



- 360° horizontal rotation
- 60° vertical sweep
- 2700lm super bright LED light source
- 300-400 meters beam distance
- IP65 waterproof rating
- Remote control and 15ft / 4.6m cable included
- ASA material, corrosion-resistant, oxidation-resistant
- Long service life
- Easy installation
- ISO 8846 / SAE J1171 Compliant
- Use the home button to instantly reset to the original installed position



White light




Warm light




Model	Control Type	Voltage	Power	Brightness	Housing Color	Color Temperature
SFSL-2700W-01W	Wired remote	10-30V	28W	2700Lumen	White	White light 5500K
SFSL-2700Y-01W						Warm light 2700K
SFSL-2700W-01B					Black	White light 5500K
SFSL-2700Y-01B						Warm light 2700K
SFSL-2700W-02W	Wireless remote	10-30V	28W	2700Lumen	White	White light 5500K
SFSL-2700Y-02W						Warm light 2700K
SFSL-2700W-02B					Black	White light 5500K
SFSL-2700Y-02B						Warm light 2700K

Up and down 60° rotation, left and right 360° rotation

### Remote Control Button Functions



**SEOUL**  
**SEOUL LED**  
 delivers high lumen output, high current operation capability, and stable, long-lasting performance.



## Remote Control LED Searchlight

SEAFLO searchlights can perform omnidirectional, multi-angle, and long-distance lighting tasks. They can rotate 360° horizontally and 60° or 75° vertically. Equipped with a remote control for user convenience, they are ideal for mariners to locate buoys, moorings, and channel markers. They are also perfect for large motorhomes and buses to pinpoint road signs, campsites, or serve as backup lighting.

### FEATURES & BENEFITS


- 360° horizontal rotation
- 60° or 75° vertical sweep
- Super bright LED light source
- 600-1200 meters beam distance
- IP65 waterproof rating

- Remote control and 15ft / 4.6m cable included
- Corrosion-resistant, oxidation-resistant material
- Long service life
- Easy installation




Model	Control Type	Voltage	Power	Candlepower	Housing Color	Color Temperature	Beam Distance
SFSL3-2000W-01W	Wired remote	10-30V	25W	125000 cd	White	White light 5500K	1968' / 600m
SFSL3-2000Y-01W						Warm light 3000K	
SFSL3-2000W-01B					Black	White light 5500K	
SFSL3-2000Y-01B						Warm light 3000K	
SFSL3-2000W-01WA	Wireless remote	10-30V	25W	125000 cd	White	White light 5500K	1968' / 600m
SFSL3-2000Y-01WA						Warm light 3000K	
SFSL3-2000W-01BA					Black	White light 5500K	
SFSL3-2000Y-01BA						Warm light 3000K	

Up and down 75° rotation, left and right 360° rotation



Model	Control Type	Voltage	Power	Candlepower	Housing Color	Color Temperature	Beam Distance
SFSL3-2700W-02W	Wired remote	10-30V	30W	180000 cd	White	White light 5500K	2624' / 800m
SFSL3-2700Y-02W						Warm light 3000K	
SFSL3-2700W-02B					Black	White light 5500K	
SFSL3-2700Y-02B						Warm light 3000K	
SFSL3-2700W-02WA	Wireless remote	10-30V	30W	180000 cd	White	White light 5500K	2624' / 800m
SFSL3-2700Y-02WA						Warm light 3000K	
SFSL3-2700W-02BA					Black	White light 5500K	
SFSL3-2700Y-02BA						Warm light 3000K	

Up and down 60° rotation, left and right 360° rotation



Model	Control Type	Voltage	Power	Candlepower	Housing Color	Color Temperature	Beam Distance
SFSL3-3500W-03W	Wired remote	10-30V	35W	230000 cd	White	White light 5500K	3937' / 1200m
SFSL3-3500Y-03W						Warm light 3000K	
SFSL3-3500W-03B					Black	White light 5500K	
SFSL3-3500Y-03B						Warm light 3000K	
SFSL3-3500W-03WA	Wireless remote	10-30V	35W	230000 cd	White	White light 5500K	3937' / 1200m
SFSL3-3500Y-03WA						Warm light 3000K	
SFSL3-3500W-03BA					Black	White light 5500K	
SFSL3-3500Y-03BA						Warm light 3000K	

Up and down 60° rotation, left and right 360° rotation





## Remote Control Halogen Searchlight

SEAFLO searchlights can perform omnidirectional, multi-angle, and long-distance lighting tasks. They can rotate 360° horizontally and 60° or 75° vertically. Equipped with a remote control for user convenience, they are ideal for mariners to locate buoys, moorings, and channel markers. They are also perfect for large motorhomes and buses to pinpoint road signs, campsites, or serve as backup lighting.

### FEATURES & BENEFITS


- 360° horizontal rotation
- 60° or 75° vertical sweep
- 260 - 420 meters beam distance
- IP65 waterproof rating
- High output halogen sealed beam lamp

- Remote control and 15ft / 4.6m cable included
- Corrosion-resistant, oxidation-resistant material
- Long service life
- Easy installation




Model	Voltage	Amps	Housing Color	Power	Candlepower	Beam Distance
SFSL1-50-01W	12V	3.6A	White	50W	100000 cd	859' / 262m
SFSL2-50-01W	24V	2A				
SFSL1-50-01B	12V	3.6A	Black			
SFSL2-50-01B	24V	2A				

Up and down 75° rotation, left and right 360° rotation



Model	Voltage	Amps	Housing Color	Power	Candlepower	Beam Distance
SFSL1-50-02W	12V	3.6A	White	50W	175000 cd	1266' / 386m
SFSL2-50-02W	24V	2A				
SFSL1-50-02B	12V	3.6A	Black			
SFSL2-50-02B	24V	2A				

Up and down 60° rotation, left and right 360° rotation



Model	Voltage	Amps	Housing Color	Power	Candlepower	Beam Distance
SFSL1-100-03W	12V	7.2A	White	100W	200000 cd	1377' / 420m
SFSL2-100-03W	24V	4A				
SFSL1-100-03B	12V	7.2A	Black			
SFSL2-100-03B	24V	4A				

Up and down 60° rotation, left and right 360° rotation



### LED Multi-Function Sport Light

Features red light (for night vision), ultraviolet (UV) light (for lures), and white light (for nighttime illumination)  
 360° horizontal rotation, 180° vertical rotation  
 IP65 waterproof rating  
 ABS+PC material, anti-oxidation, anti-impact, anti-corrosion  
 Includes versatile mount for boat or shore use  
 Powered by six AA batteries (not included).  
 Multi-purpose light ideal for fishing, boating, hunting, camping and more.




360° horizontal rotation



lighting effect


- White
- Red
- Blue



Model	Voltage	Amps	Power	Rotation Angle
SFMSL2-01	9V	0.6A	5.3W	Up and down 180° rotation, left and right 360°rotation

### LED Portable Navigation Light Kit

Includes red/green bow LED light and white all-round LED light for small boats/tenders  
 IP65 waterproof rating  
 Powered by three AAA batteries (not included)  
 Button switch for easy operation  
 ABS+PC material, anti-oxidation, impact resistance, and corrosion resistance



Navigation Light



Model	Voltage	Amps	Power	Visibility	Package includes
SFPNL2-01	4.5V	0.15A	0.7W	2NM	Bi-color bow light, Stern light, C-clamp*2, Screws*2
SFPNL2-02					Bi-color bow light, Stern light, Suction Cup*2, Screws*2
SFPNL2-08	4.5V	0.15A	0.7W	2NM	Bi-color bow light, C-clamp, Suction Cup, Screws*2
SFPNL2-09					Stern light, C-clamp, Suction Cup, Screws*2

## LED Navigation Lights 03 Series (Mini)



Blister



LED Bi-Color Bow Light 225°

Ultrasonic welding process used to enhance sealing performance



High-efficiency LED lights with low energy consumption and long lifespan

High brightness and strong light penetration



LED Red Port Light 112.5° LED Green Starboard Light 112.5°




Modular design with a simple structure

Four pry positions for easy disassembly



LED White Masthead light 225° LED White Stern Light 135°



Model	Voltage	Wattage	Angle	Housing color	Lamp color	Visibility
SFNL013-PW-03	10-30V	1.5W	112.5°	White	Red and Green	2NM
SFNL013-PB-03				Black		
SFNL013-SW-03	10-30V	1.5W	135°	White	White	3NM
SFNL013-SB-03				Black		
SFNL013-MW-03	10-30V	1.5W	225°	White	White	2NM
SFNL013-MB-03				Black		
SFNL013-LW-03	10-30V	1.5W	112.5°	White	Red	2NM
SFNL013-LB-03				Black		
SFNL013-RW-03	10-30V	1.5W	112.5°	White	Green	2NM
SFNL013-RB-03				Black		
SFNL013-BW-03	10-30V	1.5W	225°	White	Bi-Color	2NM
SFNL013-BB-03				Black		


## LED Navigation Lights 04 Series (Regular)



SFNL013-PW-04



SFNL013-PB-04



LED Red Port and Green Starboard Lights, 112.5° Each, Pair



SFNL013-MW-04

SFNL013-MB-04


LED White Masthead light 225°



SFNL013-SW-04

SFNL013-SB-04

LED White Stern Light 135°



SFNL013-LW-04

SFNL013-LB-04

LED Red Port Light 112.5°



SFNL013-RW-04

SFNL013-RB-04

LED Green Starboard Light 112.5°



SFNL013-BW-04

SFNL013-BB-04

LED Bi-Color Bow Light 225°


Model	Voltage	Wattage	Angle	Housing color	Lamp color	Visibility
SFNL013-PW-04	10-30V	1.5W	112.5°	White	Red and Green	2NM
SFNL013-PB-04				Black		
SFNL013-SW-04	10-30V	1.5W	135°	White	White	3NM
SFNL013-SB-04				Black		
SFNL013-MW-04	10-30V	1.5W	225°	White	White	2NM
SFNL013-MB-04				Black		
SFNL013-LW-04	10-30V	1.5W	112.5°	White	Red	2NM
SFNL013-LB-04				Black		
SFNL013-RW-04	10-30V	1.5W	112.5°	White	Green	2NM
SFNL013-RB-04				Black		
SFNL013-BW-04	10-30V	1.5W	225°	White	Bi-Color	2NM
SFNL013-BB-04				Black		

## LED Square Navigation Light 01 Series (Mini)

SEAFLO boat navigation lights adopt advanced LED technology, which is energy-efficient, has low power consumption, and offers a long service life, improving the safety of night navigation. They are suitable for boats with a length of less than 20 meters for night navigation and signaling.


### FEATURES & BENEFITS

- IP67 waterproof design
- Visible distance 2 nautical miles
- For boats up to 65.6 ft (20 m)
- UV resistant and corrosion resistant
- Low energy consumption and long lifespan
- High brightness and strong penetration
- Simple installation
- Super lightweight and convenient
- USCG Approval 33 CFR 183.810
- ABYC A-16, ABYC C-5, 72 COLREG Approval




Model	Voltage	Wattage	Angle	Housing color	Lamp color	Visibility
SFNL011-PW-01	12V	1W	112.5°	White	Green and Red	2NM
SFNL011-PB-01				Black		
SFNL011-SW-01	12V	1W	135°	White	White	2NM
SFNL011-SB-01				Black		
SFNL011-MW-01	12V	1W	225°	White	White	2NM
SFNL011-MB-01				Black		
SFNL011-RW-01	12V	1W	112.5°	White	Green	2NM
SFNL011-RB-01				Black		
SFNL011-LW-01	12V	1W	112.5°	White	Red	2NM
SFNL011-LB-01				Black		
SFNL011-BW-01	12V	1W	225°	White	Bi-Color	2NM
SFNL011-BB-01				Black		

## LED Square Navigation Light 02 Series (Regular)



Model	Voltage	Wattage	Angle	Housing color	Lamp color	Visibility
SFNL011-PW-02	12V	1W	112.5°	White	Green and Red	2NM
SFNL011-PB-02				Black		
SFNL011-SW-02	12V	1W	135°	White	White	2NM
SFNL011-SB-02				Black		
SFNL011-MW-02	12V	1W	225°	White	White	2NM
SFNL011-MB-02				Black		
SFNL011-RW-02	12V	1W	112.5°	White	Green	2NM
SFNL011-RB-02				Black		
SFNL011-LW-02	12V	1W	112.5°	White	Red	2NM
SFNL011-LB-02				Black		
SFNL011-BW-02	12V	1W	225°	White	Bi-Color	2NM
SFNL011-BB-02				Black		

## Horizontal Mount Lights 05 Series




SFNL033-LW-05  
LED Red Port Light 112.5°



SFNL033-RW-05  
LED Green Starboard Light 112.5°





SFNL033-PW-05  
LED Port and Starboard Lights (Pair)



Model	Voltage	Wattage	Angle	Lamp color	Visibility	Material
SFNL033-LW-05	10-30V	1.5W	112.5°	Red	2NM	ASA,PC
SFNL033-RW-05				Green		
SFNL033-PW-05	10-30V	1.5W	112.5°	Red & Green	2NM	ASA,PC

## Vertical Mount Lights 06 Series



SFNL023-SW-06  
LED White Stern Light 135°



SFNL023-PW-06  
LED Port and Starboard Lights (Pair)




SFNL023-PB-06  
LED Port and Starboard Lights (Pair)


Model	Voltage	Wattage	Angle	Housing color	Lamp color	Visibility	Material
SFNL023-SW-06	10-30V	1.5W	135°	White	White	3NM	ASA, PC
SFNL023-SB-06				Black			
SFNL023-PW-06	10-30V	1.5W	112.5°	White	Red & Green	2NM	ASA, PC
SFNL023-PB-06				Black			

## Vertical Mount Lights 05 Series

SEAFLO boat navigation lights incorporate advanced LED technology, characterized by its energy efficiency, minimal power consumption, and extended service life, thereby enhancing the safety of nighttime navigation. These lights are ideally suited for vessels with a length of less than 20 meters, facilitating night navigation and signaling.



Navigation Light



SFNL023-PS-05



SFNL023-PW-05



SFNL023-PB-05

LED Red Port Light and Green Starboard Light 112.5°, Pair

Model	Voltage	Wattage	Angle	Housing color	Lamp color	Visibility	Material
SFNL023-PW-05	10-30V	2W	112.5°	White	Red & Green	2NM	ASA,PC
SFNL023-PB-05				Black			ASA,PC
SFNL023-PS-05				S.S.316			ASA,PC,S.S.316

## Deck Mounted Navigation Lights

For boats up to 65.6 ft (20 m)  
USCG Approval 33 CFR 183.810  
ABYC A-16, ABYC C-5, 72 COLREG Approval



Blister

316 stainless steel housing, impact-resistant and seawater corrosion-resistant



LED Bi-Color Bow Light 225° (Horizontal Mount)

High-efficiency LED lights with low energy consumption and long lifespan

High brightness and strong light penetration



LED Red Port Light 112.5° (Horizontal Mount)



LED Green Starboard Light 112.5° (Horizontal Mount)

IP67 waterproof, sealed for harsh conditions





LED Red Port Light 112.5° (Vertical Mount)

Super lightweight and easy to install



LED Green Starboard Light 112.5° (Vertical Mount)




Model	Color	Voltage	Power	Angle	Visibility	Installation
SFNL031-LS-01	Red	12V	1W	112.5°	2NM	Horizontal Mount
SFNL031-RS-01	Green					
SFNL031-PS-01	Red & Green					
SFNL031-BS-01	Bi-Color	12V	1W	225°	2NM	
SFNL021-LS-01	Red	12V	1W	112.5°	2NM	Vertical Mount
SFNL021-RS-01	Green					
SFNL021-PS-01	Red & Green					

## Vertical Mount Lights 04 Series



Blister



LED Red Port Light 112.5°




LED Green Starboard Light 112.5°



Model	Voltage	Wattage	Angle	Lamp color	Visibility	Material
SFNL023-LS-04	10-30V	2W	112.5°	Red	2NM	Stainless Steel 316
SFNL023-RS-04				Green		
SFNL023-PS-04				Red & Green		

## Vertical Mount Lights 02 Series



SFNL021-LS-04  
LED Red Port Light 112.5°



SFNL021-RS-04  
LED Green Starboard Light 112.5°




SFNL021-PS-04  
LED Red Port and Green Starboard Lights, 112.5° Each, Pair



Blister

Model	Voltage	Wattage	Angle	Lamp color	Visibility	Material
SFNL021-LS-02	12V	1W	112.5°	Red	1NM	Stainless Steel 316
SFNL021-RS-02				Green		
SFNL021-PS-02				Red & Green		


### Horizontal Mount Lights 02 Series



SFNL031-SS-02 LED White Stern Light 135°  
 SFNL031-MS-02 LED White Masthead Light 225°  
 SFNL031-BS-02 LED Bi-Color Bow Light 225°

Model	Color	Voltage	Wattage	Angle	Visibility	Material
SFNL031-SS-02	White	10-30V	1.7W	135°	2NM	Stainless Steel
SFNL031-MS-02	White			225°		
SFNL031-BS-02	Bi-Color	10-30V	1.7W	225°	2NM	Stainless Steel

### Horizontal Mount Lights 03 Series



SFNL031-PS-03 LED Port and Starboard Lights (Pair)  
 SFNL031-LS-03 LED Red Port Light 112.5°  
 SFNL031-RS-03 LED Green Starboard Light 112.5°

Model	Voltage	Wattage	Angle	Lamp color	Visibility	Material
SFNL031-LS-03	12V	1.5W	112.5°	Red	1NM	S.S. 316 and PC base
SFNL031-RS-03				Green		
SFNL031-PS-03				Red & Green		

### Horizontal Mount Lights 04 Series



Model	Color	Voltage	Wattage	Angle	Visibility	Material
SFNL031-LS-04	Red	12V	1W	112.5°	2NM	Stainless Steel 316
SFNL031-RS-04	Green					
SFNL031-PS-04	Red & Green	12V	1W	112.5°	2NM	Stainless Steel 316
SFNL031-BS-04	Bi-Color	12V	1W	225°	2NM	Stainless Steel 316

### LED Bi-Color Bow Light



Model	Voltage	Wattage	Angle	Lamp color	Visibility	Material
SFNL051-01S	12V	0.7W	225°	Bi-Color	1NM	Chrome-plated zinc
SFNL053-01S	10-30V	2W			2NM	Stainless Steel 316

### LED All-Round Lights 01 Series



Model	Voltage	Wattage	Angle	Lamp color	Certificate	Material
SFNL073-WB-01	10-30V	3W	360°	White	USCG 3NM	Plastic
SFNL073-GB-01				Green	USCG 2NM	
SFNL073-RB-01				Red	USCG 2NM	


## LED All-Round Pole Lights

SEAFLO All-Round LED Nav lights offer outstanding durability and longevity while sipping battery power. This versatile light combines 2-mile or 3-mile, 360° light visibility for boats up to 65.6ft (20m) with adjust ability. Pole fits most popular bases (can be sold separately).

USCG, ABYC C-5, 72 COLREG Approval



## LED All-Round Lights 02 Series



Overall Length	2.4" (61mm)					
Model	SFNL073-WB-02	SFNL073-RB-02	SFNL073-GB-02	SFNL073-WW-02	SFNL073-RW-02	SFNL073-GW-02
Voltage	10-30V	10-30V	10-30V	10-30V	10-30V	10-30V
Visibility	2NM	2NM	2NM	2NM	2NM	2NM
Wattage	1.5W	1.5W	1.5W	1.5W	1.5W	1.5W
Lighting color	White 360°	Red 360°	Green 360°	White 360°	Red 360°	Green 360°
Housing color	Black	Black	Black	White	White	White
Material	ASA,PC					

## LED All-Round Pole Lights 05 Series (Fixed mount)



Overall Length	2.15"(54.5mm)		6"(152mm)		8"(205mm)	
Model	SFNL083-2-05B	SFNL083-2-05W	SFNL083-6-05B	SFNL083-6-05W	SFNL083-8-05B	SFNL083-8-05W
Voltage	10-30V	10-30V	10-30V	10-30V	10-30V	10-30V
Visibility	2NM	2NM	2NM	2NM	2NM	2NM
Wattage	1.5W	1.5W	1.5W	1.5W	1.5W	1.5W
Housing Color	Black	White	Black	White	Black	White
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Base Type	Surface mount		Fixed mount		Fixed mount	
Material	ASA,PC		ASA,PC		ASA,PC,316 stainless steel	

## LED All-Round Pole Lights 05 Series (Adjustable Mount)

### Plastic Base



Overall Length	8"(205mm)		12"(315mm)		20"(510mm)	
Model	SFNL083-8A-05BP	SFNL083-8A-05WP	SFNL083-12-05BP	SFNL083-12-05WP	SFNL083-20-05BP	SFNL083-20-05WP
Voltage	10-30V		10-30V		10-30V	
Visibility	2NM		2NM		2NM	
Wattage	1.5W		1.5W		1.5W	
Base Type	Adjustable mount		Adjustable mount		Adjustable mount	
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Housing Color	Black housing	White housing	Black housing	White housing	Black housing	White housing

### 316 Stainless Steel Base



Overall Length	8"(205mm)		12"(315mm)		20"(510mm)	
Model	SFNL083-8A-05BS	SFNL083-8A-05WS	SFNL083-12-05BS	SFNL083-12-05WS	SFNL083-20-05BS	SFNL083-20-05WS
Voltage	10-30V		10-30V		10-30V	
Visibility	2NM		2NM		2NM	
Wattage	1.5W		1.5W		1.5W	
Base Type	Adjustable mount		Adjustable mount		Adjustable mount	
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Housing Color	Black housing	White housing	Black housing	White housing	Black housing	White housing



Overall Length	24"(605mm)		34"(865mm)		40"(1015mm)	
Model	SFNL083-24A-05BP	SFNL083-24A-05WP	SFNL083-34-05BP	SFNL083-34-05WP	SFNL083-40-05BP	SFNL083-40-05WP
Voltage	10-30V		10-30V		10-30V	
Visibility	2NM		2NM		2NM	
Wattage	1.5W		1.5W		1.5W	
Base Type	Adjustable mount		Adjustable mount		Adjustable mount	
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Housing Color	Black housing	White housing	Black housing	White housing	Black housing	White housing




Overall Length	24"(605mm)		34"(865mm)		40"(1015mm)	
Model	SFNL083-24A-05BS	SFNL083-24A-05WS	SFNL083-34-05BS	SFNL083-34-05WS	SFNL083-40-05BS	SFNL083-40-05WS
Voltage	10-30V		10-30V		10-30V	
Visibility	2NM		2NM		2NM	
Wattage	1.5W		1.5W		1.5W	
Base Type	Adjustable mount		Adjustable mount		Adjustable mount	
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Housing Color	Black housing	White housing	Black housing	White housing	Black housing	White housing

All-Round Pole Lights


## LED All-Round Pole Lights 05 Series Plug-in Mount

### Plastic Base



Overall Length	24"(605mm)		42"(1080mm)		54"(1380mm)	
Model	SFNL083-24P-05BP	SFNL083-24P-05WP	SFNL083-42-05BP	SFNL083-42-05WP	SFNL083-54-05BP	SFNL083-54-05WP
Voltage	10-30V		10-30V		10-30V	
Visibility	2NM		2NM		2NM	
Wattage	1.5W		1.5W		1.5W	
Base Type	Plug-in mount		Plug-in mount		Plug-in mount	
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Housing Color	Black housing	White housing	Black housing	White housing	Black housing	White housing

### 316 Stainless Steel Base



Overall Length	24"(605mm)		42"(1080mm)		54"(1380mm)	
Model	SFNL083-24P-05BS	SFNL083-24P-05WS	SFNL083-42-05BS	SFNL083-42-05WS	SFNL083-54-05BS	SFNL083-54-05WS
Voltage	10-30V		10-30V		10-30V	
Visibility	2NM		2NM		2NM	
Wattage	1.5W		1.5W		1.5W	
Base Type	Plug-in mount		Plug-in mount		Plug-in mount	
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Housing Color	Black housing	White housing	Black housing	White housing	Black housing	White housing

# LED All-round Pole Lights 06 Series

## Plug-in Mount, Angled

The inclination angle of the lamp post is 150°




Plastic



316 Stainless Steel

### Plastic Base



### 316 Stainless Steel Base



Overall Length	24"(605mm)		42"(1080mm)		54"(1380mm)	
Model	SFNL083-24-06BP	SFNL083-24-06WP	SFNL083-42-06BP	SFNL083-42-06WP	SFNL083-54-06BP	SFNL083-54-06WP
Voltage	10-30V		10-30V		10-30V	
Visibility	2NM		2NM		2NM	
Wattage	1.5W		1.5W		1.5W	
Base Type	Plug-in mount		Plug-in mount		Plug-in mount	
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Housing Color	Black housing	White housing	Black housing	White housing	Black housing	White housing


Overall Length	24"(605mm)		42"(1080mm)		54"(1380mm)	
Model	SFNL083-24-06BS	SFNL083-24-06WS	SFNL083-42-06BS	SFNL083-42-06WS	SFNL083-54-06BS	SFNL083-54-06WS
Voltage	10-30V		10-30V		10-30V	
Visibility	2NM		2NM		2NM	
Wattage	1.5W		1.5W		1.5W	
Base Type	Plug-in mount		Plug-in mount		Plug-in mount	
Color Temperature	Daylight white 5700K		Daylight white 5700K		Daylight white 5700K	
Housing Color	Black housing	White housing	Black housing	White housing	Black housing	White housing

## Mounting Base for Plug-in Mount Pole Lights

SEAFLO Plug-In Light Base is a dependable, easy to use base for an pole light (sold separately). The innovative design ensures the pole inserts with a tight and secure fit, and it prevents rattling while the boat is underway or during trailering.




Model	SFPB-04	SFPB-04S	SFPB-05	SFPB-05S
Base Type	Straight base	Straight base	Angled base	Angled base
Material	Plastic	316 stainless steel and Plastic	Plastic	316 stainless steel and Plastic
Size	3.34" x 1.89" x 2.30" (85mm x 48mm x 58.5mm)		3.34" x 1.89" x 2.30" (85mm x 48mm x 58.5mm)	
Fits	05 and 06 series LED all-round pole lights (plug-in mount)			



## LED Bi-Color Bow Lights


Whether at anchor or underway, it's important your navigation lights are both functional and clearly visible to nearby boaters. This super-bright, sealed-for-life nav light is strong for a long and dependable life on the bow. The high-efficiency LED bi-color lamp has red and green LEDs, with a sector angle of 112.5° each, and is for use on the bow of sailboats and power-craft. It can be used in place of traditional sidelights or incandescent bow-lights. These lamps are designed to be mounted on a vertical surface.

Model:	SFNL051-11B-03B
Overall Length:	11-1/8" (282mm)
Voltage:	12 V
Visibility:	1NM
Wattage:	2W
Base Type:	Plug-in mount (w / SS Straight base)
Material:	Plastic+Stainless Steel




## LED All-Round Pole Lights 04 Series

Color Temperature: Daylight white 4000-4500K  
LED All-Round Light use for boats up to 65.6 ft (20m)




Overall Length	9.5" (247mm)	12" (305mm)	23.6" (600mm)
Model	SFNL083-9-04B	SFNL083-12-04B	SFNL083-24-04B
Voltage	10-30V	10-30V	10-30V
Visibility	2NM	2NM	2NM
Wattage	1W	1W	1W
Base Type	Adjustable mount	Adjustable mount	Adjustable mount
Material	Plastic+Stainless Steel		





Overall Length	6" (152mm)	15" (381mm)	22" (557mm)	27"~41" (695~1050mm)
Model	SFNL083-6-04B	SFNL083-15-04B	SFNL083-22-04B	SFNL083-41-04B
Voltage	10-30V	10-30V	10-30V	10-30V
Visibility	2NM	2NM	2NM	2NM
Wattage	1W	1W	1W	1W
Base Type	Fixed mount	Adjustable mount	Plug-in Mount	Plug-in Mount
Material	Plastic+Stainless Steel	Plastic+Stainless Steel	Plastic+Stainless Steel	Plastic+Aluminum pole

## LED All-Round Pole Lights 02 Series

Color Temperature: Daylight white 4000-4500K  
LED All-Round Light use for boats up to 65.6 ft (20m).



Overall Length	4" (106mm)	7-1/2" (186mm)	9-1/4" (235mm)	25" (635mm)
Model	SFNL081-4-02B	SFNL081-7-02B	SFNL081-9-02B	SFNL081-25-02B
Voltage	12V	12 V	12 V	12 V
Visibility	2NM	2NM	2NM	2NM
Wattage	1.5W	1.5W	1.5W	1.5W
Base Type	Fixed mount	Fixed mount	Adjustable mount	Adjustable mount
Material	Plastic+Stainless Steel			



Overall Length	12" (305mm)	16" (396mm)	24" (593mm)	36" (898mm)	28-1/4"~44" (750~1110mm)
Model	SFNL081-12-02B	SFNL081-16-02B	SFNL081-24B-02B	SFNL081-36-02B	SFNL081-44-02B
Voltage	12 V	12 V	12 V	12 V	12 V
Visibility	2NM	2NM	2NM	2NM	2NM
Wattage	1.5W	1.5W	1.5W	1.5W	1.5W
Base Type	Adjustable mount	Adjustable mount	Plug-in mount with straight base	Plug-in mount	Plug-in mount
Material:	Plastic+Stainless Steel				Plastic+Aluminum

## LED All-Round Pole Lights 03 Series

Material: Plastic+Stainless Steel  
 Color Temperature: Daylight white 4000-4500K  
 LED All-Round Light use for boats up to 65.6 ft (20m)



Overall Length	2-4/5" (71mm)	4-7/8" (124mm)	4-7/8" (124mm)	9-1/2" (248mm)	12-1/2" (318mm)
Model	SFNL083-2-03B	SFNL083-5-03B	SFNL083-5-03W	SFNL083-9-03B	SFNL083-12-03B
Voltage	12-24V	12-24V	12-24V	12-24V	12-24V
Visibility	3NM	3NM	3NM	3NM	3NM
Wattage	2.5W	2.5W	2.5W	2.5W	2.5W
Base Type	/	Fixed mount	Fixed mount	Adjustable mount	Fixed mount



Overall Length	16" (403mm)	25" (642mm)	24" (600mm)	36" (905mm)	24" (600mm)
Model	SFNL083-16-03B	SFNL083-25-03B	SFNL083-24-03B	SFNL083-36-03B	SFNL083-24B-03B
Voltage	12-24V	12-24V	12-24V	12-24V	12-24V
Visibility	3NM	3NM	3NM	3NM	3NM
Wattage	2.5W	2.5W	2.5W	2.5W	2.5W
Base Type	Adjustable mount	Adjustable mount	Plug-in mount	Plug-in mount	Plug-in mount (w/Straight base)


## LED All-Round Pole Lights 01 Series



Overall Length	4" (99mm)	10" (259mm)	12" (293mm)
Model	SFNL061-4-01B	SFNL061-10-01B	SFNL061-12-01B
Voltage	12V	12V	12V
Visibility	2NM	2NM	2NM
Wattage	3.1W	3.1W	3.1W
Base Type	Fixed mount	Adjustable mount	Fixed mount
Bulb Type	LED	LED	LED
Material	Plastic	Plastic+Stainless steel	Plastic+Stainless steel

## Mounting Base for Plug-in Mount Pole Lights

Compatible with 02, 03, and 04 series LED all-round pole lights (plug-in mount)



Model	SFPB-01S	SFPB-01	SFPB-03	SFPB-02
Base Type	Straight base	Straight base	Angled base	Angled base
Material	Stainless Steel and PC	Plastic	Plastic	Plastic
Size	2.1" x 2.1" x 2.6" (53 x 53 x 66.4 mm)	2.7" x 2.0" x 3.1" (68 x 50 x 80mm)	2.7" x 2.0" x 3.4" (68 x 50 x 86mm)	3.8" x 1.6" x 2.6" (97 x 41 x 65mm)

All-Round Pole Lights


316 STAINLESS STEEL COVER IP68



Single package A pair of packages

### LED Underwater Lights

SEAFLO LED underwater light is made of marine-grade 316 stainless steel and high-strength engineering plastic, designed to withstand harsh marine environments. It is vibration and shock resistant. The light features a waterproof design with an IP68 rating. There are various styles and colors available to choose from. High-intensity lighting makes your boat more visible, enhancing safety during night activities.



### Underwater Lights 02 Series (3 LEDs)



SFUL1-3W-02 SFUL1-3B-02 SFUL1-3G-02 SFUL1-3R-02 RGBW

Model	Light Color	Voltage	Power	Lumens	Beam Angle	Size	Quantity
SFUL1-3W-02	White	12V	9W	800lm	80°	Ø2.87"	Single
SFUL1-3B-02	Blue	12V	9W	800lm	80°	Ø2.87"	Single
SFUL1-3G-02	Green	12V	9W	800lm	80°	Ø2.87"	Single
SFUL1-3R-02	RGBW	12V	3.5W	9-40lm	80°	Ø2.87"	Single
SFUL1-3W-02P	White	12V	9W	800lm	80°	Ø2.87"	Pair
SFUL1-3B-02P	Blue	12V	9W	800lm	80°	Ø2.87"	Pair
SFUL1-3G-02P	Green	12V	9W	800lm	80°	Ø2.87"	Pair
SFUL1-3R-02P	RGBW	12V	3.5W	9-40lm	80°	Ø2.87"	Pair


### Underwater Lights 02 Series (6 LEDs)




SFUL1-6W-02 SFUL1-6B-02 SFUL1-6G-02 SFUL1-6R-02 RGBW

Model	Light Color	Voltage	Power	Lumens	Beam Angle	Size	Quantity
SFUL1-6W-02	White	12V	18W	1350lm	80°	Ø3.59"	Single
SFUL1-6B-02	Blue	12V	18W	1350lm	80°	Ø3.59"	Single
SFUL1-6G-02	Green	12V	18W	1350lm	80°	Ø3.59"	Single
SFUL1-6R-02	RGBW	12V	7W	18-85lm	80°	Ø3.59"	Single
SFUL1-6W-02P	White	12V	18W	1350lm	80°	Ø3.59"	Pair
SFUL1-6B-02P	Blue	12V	18W	1350lm	80°	Ø3.59"	Pair
SFUL1-6G-02P	Green	12V	18W	1350lm	80°	Ø3.59"	Pair
SFUL1-6R-02P	RGBW	12V	7W	18-85lm	80°	Ø3.59"	Pair

LED Underwater Lights




Underwater Lights 01 Series (6 LEDs)




Model	Light Color	Voltage	Power	Lumens	Beam Angle	Size
SFUL1-6W-01	White	12V	18W	1350lm	80°	5" length
SFUL1-6B-01	Blue	12V	18W	1350lm	80°	5" length
SFUL1-6G-01	Green	12V	18W	1350lm	80°	5" length

Underwater Lights 01 Series (3 LEDs)




Model	Light Color	Voltage	Power	Lumens	Beam Angle	Size
SFUL1-3W-01	White	12V	9W	800lm	80°	4" length
SFUL1-3B-01	Blue	12V	9W	800lm	80°	4" length
SFUL1-3G-01	Green	12V	9W	800lm	80°	4" length

Underwater Lights 01 Series (12 LEDs)




Model	Light Color	Voltage	Power	Lumens	Beam Angle	Size
SFUL1-12W-01	White	12V	36W	1650lm	80°	6" length
SFUL1-12B-01	Blue	12V	36W	1650lm	80°	6" length
SFUL1-12G-01	Green	12V	36W	1650lm	80°	6" length

### LED Floodlights 03 Series (Bracket Mount)



Model	SFFL3-550W-03W	SFFL3-550W-03B	SFFL3-450Y-03W	SFFL3-450Y-03B
Voltage	12/24V		12/24V	
Power	6W		6W	
Color Temperature	5000K (White)		3000K (Warm White)	
Luminous Flux	550 lm		550 lm	
Housing Color	White	Black	White	Black
Installation	Bracket Mount		Bracket Mount	
Material	Thermally Conductive Nylon + PC + 316 Stainless Steel		Thermally Conductive Nylon + PC + 316 Stainless Steel	
Cable	2.5m		2.5m	

### LED Floodlights 04 Series (Flush Mount)



Model	SFFL3-550W-04W	SFFL3-550W-04B	SFFL3-450Y-04W	SFFL3-450Y-04B
Voltage	12/24V		12/24V	
Power	6W		6W	
Color Temperature	5000K (White)		3000K (Warm White)	
Luminous Flux	550 lm		550 lm	
Housing Color	White	Black	White	Black
Installation	Flush Mount		Flush Mount	
Material	Thermally Conductive Nylon + PC		Thermally Conductive Nylon + PC	
Cable	0.5m		0.5m	

### LED Floodlights 02 Series (Bracket Mount)



Model	Voltage	Power	Color Temperature	Luminous Flux	Housing Color	Material	Cable
SFFL3-1500WW-02W	12/24V	15W (High-Intensity Mode)	5000K (White)	1500 lm	White	Thermally Conductive Nylon + PC + 316 Stainless Steel	2.5m
SFFL3-1500WW-02B		3W (Low-Intensity Mode)			Black		

### Dual Colour LED Floodlights 01 Series Bracket Mount






Model	Voltage	Power	Color Temperature	Luminous Flux	Housing Color	Material	Cable
SFFL3-850WB-01W	12/24V	10W (White LEDs) 4W (Blue LEDs)	5000K (White)	850 lm	White	Thermally Conductive Nylon + PC + 316 Stainless Steel	2.5m
SFFL3-850WB-01B					Black		
SFFL3-850WR-01W		10W (White LEDs) 2W (Red LEDs)	5000K (White)		White		
SFFL3-850WR-01B					Black		
SFFL3-850WY-01W		10W (White LEDs) 3W (Warm White LEDs)	5000K (White) 2700K (Warm White)		White		
SFFL3-850WY-01B					Black		



Flush Mount Bracket Mount


### LED Floodlights 3 LEDs



Efficient Heat Dissipation






240° Adjustable Design






Model	SFFL3-750W-05W	SFFL3-750W-05B	SFFL3-750W-06W	SFFL3-750W-06B
Voltage	12/24V		12/24V	
Power	12W		12W	
Color Temperature	White light 5000K		White light 5000K	
Luminous Flux	750 lm		750 lm	
Beam Angle	45°		45°	
Housing Color	White	Black	White	Black
Material	PC+Aluminium		PC+Aluminium+316 Stainless Steel	

### LED Floodlights 6 LEDs



Model	SFFL3-1500W-05W	SFFL3-1500W-05B	SFFL3-1500W-06W	SFFL3-1500W-06B
Voltage	12/24V		12/24V	
Power	24W		24W	
Color Temperature	White light 5000K		White light 5000K	
Luminous Flux	1500 lm		1500 lm	
Beam Angle	45°		45°	
Housing Color	White	Black	White	Black
Material	PC+Aluminium		PC+Aluminium+316 Stainless Steel	

### LED Floodlights 12 LEDs



Model	Voltage	Power	Color Temperature	Luminous Flux	Beam Angle	Material	Housing Color
SFFL3-3000W-06W	12/24V	24W	White light 5000K	3000 lm	45°	PC+Aluminium+316 Stainless Steel	White
SFFL3-3000W-06B							Black



## LED Floodlights

Exquisite, high-quality LEDs grace seaflo floodlight, delivering unparalleled maximum light output that floods your surroundings with brilliant illumination, while simultaneously demonstrating remarkable energy efficiency. Perfectly suited for marine environments, these LEDs ensure both safety and aesthetic appeal on the water.

**CREE LED**  
high-lumen chips, long-lasting high intensity, stable lighting performance





## LED Floodlights 07 Series (Bracket Mount)




SFLL3-1000W-07BL  
SFLL3-800Y-07BL

SFLL3-1000W-07WL  
SFLL3-800Y-07WL



SFLL3-1000W-07BC  
SFLL3-800Y-07BC

SFLL3-1000W-07WC  
SFLL3-800Y-07WC



316 stainless steel bracket

Model	Lens Type	Voltage	Power	Color Temperature	Luminous Flux	Housing Color	Material	Cable
SFLL3-1000W-07BL	Long Range	12/24V	15W	5700K (White)	1000 lm	Black	Aluminium+ 316 Stainless Steel	0.3m
SFLL3-1000W-07WL				White				
SFLL3-800Y-07BL				3000K (Warm White)	800 lm	Black		
SFLL3-800Y-07WL				White				
SFLL3-1000W-07BC	Close Range	12/24V	15W	5700K (White)	1000 lm	Black		
SFLL3-1000W-07WC				White				
SFLL3-800Y-07BC				3000K (Warm White)	800 lm	Black		
SFLL3-800Y-07WC				White				

## LED Floodlights 08 Series (Bracket Mount)




Efficient heat dissipation 240° adjustable bracket



SFLL3-2400W-08BL  
SFLL3-2100Y-08BL

SFLL3-2400W-08WL  
SFLL3-2100Y-08WL





316 stainless steel bracket



SFLL3-2400W-08BC  
SFLL3-2100Y-08BC

SFLL3-2400W-08WC  
SFLL3-2100Y-08WC




Model	Lens Type	Voltage	Power	Color Temperature	Luminous Flux	Housing Color	Material	Cable
SFLL3-2400W-08BL	Long Range	12/24V	30W	5700K (White)	2400 lm	Black	Aluminium+ 316 Stainless Steel	0.3m
SFLL3-2400W-08WL				White				
SFLL3-2100Y-08BL				3000K (Warm White)	210 lm	Black		
SFLL3-2100Y-08WL				White				
SFLL3-2400W-08BC	Close Range	12/24V	30W	5700K (White)	2400 lm	Black		
SFLL3-2400W-08WC				White				
SFLL3-2100Y-08BC				3000K (Warm White)	210 lm	Black		
SFLL3-2100Y-08WC				White				

## LED Deck Lights

High quality LEDs for maximum light output and energy efficiency.




Blister



Model	Voltage	LED Wattage	Effective Wattage	Mount Type	Color Temperature	Material
SFDL1-WA-01	10-30 V	18W	14W	Bracket mount	White (5500-6300K)	Aluminum

## LED Stern Light 02 Series

Electropolished 316 stainless steel cover  
Bright LED design, long lifespan, and low power consumption  
Watertight construction designed to resist corrosion  
Thin design with high durability




Model	SFNL043-W-02	SFNL043-Y-02	SFNL043-B-02
Voltage	10-30V		
Wattage	2W		
Visibility	3NM		
Angle	135°		
Lighting color	Cool White	Warm White	Blue
Material	Stainless Steel 316		

## LED Stern Light 01 Series



Blister



Model	SFNL041-W-01	SFNL041-Y-01	SFNL041-B-01
Voltage	12V		
Wattage	2.2W		
Visibility	2NM		
Angle	135°		
Lighting color	Cool White	Warm White	Blue
Material	S.S.304		


## LED Ceiling Light



Model	Voltage	Wattage	Power	Installation Method	Color Temperature	Material
SFCL1-3-WS-01	12V	1W	6x0.2W	Flush mount	Cool White (5500-6300K)	PC White
SFCL1-3-YS-01					Warm White(2900-3000K)	PC White
SFCL1-3-BS-01					Blue	PC+S.S.304
SFCL1-3-RS-01					Red	PC+S.S.304


## LED Strip Light

These strip lamps provide a soft and uniform courtesy light pattern in white, warm white, blue or red. The range is ideal for interior or exterior applications including storage lockers, under cabinetry, under gunnels and more. The sealed switch system prevents moisture and other contaminants from affecting electronics. Surface mount installation with fastenings in each end of the lamp body are covered by snap-on end caps for a clean and modern appearance.



Model	Voltage	Wattage	Mount Type	Color Temperature	Switch	Material	Size
SFSL1-WW-01	12V	4W	Surface mount	White (4000-4500K)	NO	Plastic	9-3/8"/240mm
SFSL1-WW-01S				White (4000-4500K)	YES		
SFSL1-XW-01S				White+Blue	YES		
SFSL1-ZW-01S				White+Red	YES		

## LED Ceiling Light



Lens 3 inch



SFCL1-4-WC-02



SFCL1-4-WS-02

Model	Voltage	Wattage	LED Power	Installation Method	Color Temperature	Diameter	Material
SFCL1-4-WC-02	12V	3.6W	20 × 0.2W	Surface mount	White (5500-6300K)	4-1/6" (106.6mm)	Brass
SFCL1-4-WS-02							S.S.304



Lens 4 inch



Blister



SFCL1-5-WC-02




SFCL1-5-WS-02



SFCL1-5-ZS-02

Model	Voltage	Wattage	LED Power	Installation Method	Color Temperature	Diameter	Material
SFCL1-5-WC-02	12V	3.6W	20 × 0.2W	Surface mount	White (5500-6300K)	5-3/8" (137mm)	Brass
SFCL1-5-WS-02					White (5500-6300K)		S.S.304
SFCL1-5-ZS-02					Red/White (5500-6300K)		S.S.304



Lens 5 inch



SFCL1-6-WC-02



SFCL1-6-WS-02



SFCL1-6-WS-03



SFCL1-6-ZS-03

Model	Voltage	Wattage	LED Power	Installation Method	Color Temperature	Diameter	Material
SFCL1-6-WC-02	12V	3.6W	20 × 0.2W	Surface mount	White (5500-6300K)	6-5/8" (168mm)	Brass
SFCL1-6-WS-02					White (5500-6300K)		S.S.304
SFCL1-6-WS-03					White (5500-6300K)		S.S.304
SFCL1-6-ZS-03					Red/White (5500-6300K)		

## LED Ceiling Light

This is ceiling Light with beautiful appearance and accent. This simple and stylish dome Light is pre-wired with an integral built-in mini on/off rocker switch. With weather proof design, this stylish ceiling light can be used normally in severe environment. It can be surface-mounted on any flat ceiling surface, simple and quick Installation. These lights are going to be a great addition to your RV, boat or even your room.



SFCL1-3-WW-01




SFCL1-3-YW-01



SFCL1-3-BW-01




Blister



Model	Voltage	Wattage	Power	Installation Method	Color Temperature	Material
SFCL1-3-WW-01	12V	1W	6 × 0.2W	Flush mount	Cool White (5500-6300K)	PC White
SFCL1-3-YW-01					Warm White (2900-3200K)	
SFCL1-3-BW-01					Bule	

## LED Ceiling Light



Blister



SFCL1-4-YW-04



SFCL1-4-WW-04



SFCL1-5-YW-04



SFCL1-5-WW-04


Model	Voltage	Wattage	Installation Method	Color Temperature	Diameter
SFCL1-4-YW-04	10-30V	4W	Surface mount	Warm White (2900-3200K)	4" (102mm)
SFCL1-4-WW-04				White (5800-6300K)	
SFCL1-5-YW-04	10-30V	6W	Surface mount	Warm White (2900-3200K)	5" (127mm)
SFCL1-5-WW-04				White (5800-6300K)	

## LED Courtesy Light



Model	Voltage	Wattage	Power	Installation Method	Color Temperature
SFCL1-WS-04	12V	0.2W	1 × 0.2W	Flush mount	Cool White (5500-6300K)
SFCL1-BS-04					Blue
SFCL1-YS-04					Warm White (2800-3200K)
SFCL1-CS-04	12V	0.2W	4 × 0.2W	Flush mount	Multi-Color


## LED Oblong Courtesy Light



Model	Voltage	Wattage	Power	Installation Method	Material	Cool
SFCL3-WS-01	12-24V	0.5W	3x0.2W	Flush mount	S.S. 316 and PC base	Cool White (5500-6300K)
SFCL3-YS-01						Warm White(2900-3200K)
SFCL3-BS-01						Blue

## LED Courtesy Light

LED courtesy lights are versatile lighting solutions suitable for both daytime and nighttime use. They provide safe, reliable and energy efficient lighting for interior or exterior applications, effectively highlighting specific areas within your vessel.



Model	Voltage	Wattage	Power	Installation Method	Color Temperature	Material
SFCL1-WS-03	12V	0.4W	4×0.2W	Surface mount	Cool White(5500-6300K)	PC+Stainless Steel
SFCL1-YS-03					Warm White(2800-3200K)	
SFCL1-WS-02	12V	1.2W	6×0.2W	Surface mount	Cool White(5500-6300K)	S.S. 304
SFCL1-BS-02					Blue	

## LED Livewell Light

LED Livewell Light will illuminate your livewell and small utility area. Can be used above or below water level with through-wall mounting. IP68 waterproof, Completely sealed, power saving LED Livewell / Baitwell lamps are designed for installation into live bait tanks.




Model	Voltage	Wattage	Power	Installation Method	Color Temperature	Material
SFCL1-WB-05	12V	0.2W	1×0.2W	Flush mount	Cool White(5500-6300K)	PC
SFCL1-BB-05					Blue	
SFCL1-WB-06	12V	0.2W	1×0.2W	Flush mount	Cool White(5500-6300K)	PC
SFCL1-WB-06					Blue	

## LED Reading Light

SEAFLO LED reading lamp is an elegantly stylish wall mounted LED interior lamp perfect for any vessel. The stainless steel or brass lacquered body offers a premium look and feel, while the unique constant friction mechanism offers adjustable swing and pitch to achieve optimum light angles, that won't need constant adjustment. The reading lamp is available in warm (2900K-3200k) which will beautifully enhance the materials chosen for your vessel.



Blister



Model	Voltage	Wattage	Power	Installation Method	Color Temperature	Material
SFRL3-S-03	8-30V	3.1W	1 × 3W	Surface mount	Warm White	Stainless Steel
SFRL3-C-02					Warm White	Brass Lacquered
SFRL3-S-01	12V	3.1W	/	Surface mount	Warm White (2900-3200K)	Stainless Steel



**Stainless Steel or Brass Lamp Body**

Corrosion-resistant, no rust and no fading



**Lamp Beads**

Lamp beads adopt high-power chips. high brightness, uniform light emission, and high color rendering index.



**Switch button**

Base There is a switch button at the bottom, and the heat dissipation design is added, and the heat dissipation performance is better.